

# DS-L 420


## Dry Swab - Laser Cut

420 samples in 60 minutes -  
we automate your dry swab sample transfer processing!

### OUR IDEA

- High precision
- High efficiency
- High speed
- Seamless traceability
- Flexible and highly adaptable IT communication
- Cloud-based functions and data exchange
- Easy maintenance
- Great accessibility
- Expandable frameworks for new tasks





# DS-L 420


Our answer to COVID-19 - but you can use it for all dry swab samples with plastic tubes.

It is a highly efficient stand-alone system for the automatic opening, transferring and laser cutting of dry swabs.

## THE PROCESS

- Acquisition of the individual samples by scanning the 1-2D code and assigning the samples to a customer order
- Opening the sample by pulling the swab out of its plastic tube
- Aligning and transferring the swab into the DeepWell plate 96
- Laser cutting the applicator tip
- Disposing the leftover swab
- Highly efficient and accessible IT system with data exchange, FDA 21 audit trail and electronic signature functionality





# DS-L 420

## FUNCTION OVERVIEW


### Our DS-L 420 can handle:

- ✓ all common COVID-19 dry swab sample sizes
- ✓ screwed-lid & snapped-lid samples

### Special features:

- ✓ 2 large doors guarantee great access to the system
- ✓ a Hepa 14 filter system including UVC-light
- ✓ UVC cleaning the tube Adjustment after each contact
- ✓ Carryover and contamination free – the DeepWell plate 96 is covered at all times
- ✓ CO<sub>2</sub>-Laser for contact-free cutting
- ✓ air extraction while laser cutting (Hepa 14)
- ✓ easy moveable with hydraulic rollers
- ✓ no compressed air needed
- ✓ CE certified





## Product specifications

<b>Model</b>	<b>DS-L 420</b>	
Dimensions	1800x840x2000mm (LxWxH)	
Weight	480 kg	
Electrical requirements	Power	3 Phase 400V,N,PE
	Hz	50-60Hz
	Power Consumption	~10KW
Operating requirements	Temperature	15°C – 35°C
	Relative Humidity	20% RH – 80% RH (non-condensing)
	Atmospheric Pressure	80 kPa – 106 kPa
Functions	Sample Barcode identification, lid opening, CO2-Laser cutting, HEPA 14 filtration with UVC-light included, flexible and adaptive integration, hydraulic rollers, FDA conform logging functionality, customer IT interface etc.	
Throughput	420 samples / 60 minutes	

**Contact us:**

**D&T Engineering GmbH**

[p.feldl@dt-gmbh.com](mailto:p.feldl@dt-gmbh.com)

Peter Feldl

Neuhaus 4

+49 (0) 170 9975343

D-84539 Ampfing

[www.dt-gmbh.com](http://www.dt-gmbh.com)